

# Belt Sorting System

Designed for high capacity applications, the system uses TAIHO's CCD imaging system to delivering exceptional sorting accuracy.



## SPECIFICATIONS

MODEL*	6SXL-300KD2Y	6SXL-600KD2Y	6SXL1200KD2Y	6SXL-300ZD2Y	6SXL-600ZD2Y	6SXL-1200ZD2Y
Channels	63	126	252	63	126	252
Power (kW)	2.5	2.8	4.5	2.5	2.8	4.5
Supply Voltage (V)	220V/50hz	220V/50hz	220V/50hz	220V/50hz	220V/50hz	220V/50hz
Air Pressure (MPa)	0.4 - 0.6	0.4 - 0.6	0.4 - 0.6	0.4 - 0.6	0.4 - 0.6	0.4 - 0.6
Air Consumption (m <sup>3</sup> /mm)	0.5 - 1.0	0.8 - 1.5	1.2 - 2.1	0.5 - 1.0	0.8 - 1.5	1.2 - 2.1
External Dimensions (mm)	3530x1760x2066	3530x2100x2066	3530x2700x2066	3325x1315x1520	3325x1630x1520	3325x2260x1520
Weight (kg)	800	1080	1510	400	600	1070
Output (t/h)	1.5 - 3.0	3.0 - 5.5	5.0 - 11.0	1.5 - 3.0	3.0 - 5.5	5.0 - 11.0
Sorting Accuracy (%)	>99	>99	>99	>99	>99	>99
Optimal Ratio of carryover	>8:1	>8:1	>8:1	>8:1	>8:1	>8:1



call 1800 354 302  
visit [inspectionsystems.com.au](http://inspectionsystems.com.au)

Australia Freecall: 1800 354 302 | 273 Holt Parade Thomastown Victoria 3074  
New Zealand Freecall: 0800 777 704 | Unit 2/549 Halswell Junction Road Hornby Christchurch

